

## Heap Memory – Allocating Arrays

```

heap-puzzle3.cpp
5 int *x;
6 int size = 3;
7
8 x = new int[size];
9
10 for (int i = 0; i < size; i++) {
11     x[i] = i + 3;
12 }
13
14 delete[] x;

```

\*: **new[]** and **delete[]** are identical to **new** and **delete**, except the constructor/destructor are called on each object in the array.

## Memory and Function Calls

Suppose we want to join two Cubes together:

```

joinCubes-byValue.cpp
11 /*
12  * Creates a new Cube that contains the exact volume
13  * of the volume of the two input Cubes.
14  */
15 Cube joinCubes(Cube c1, Cube c2) {
16     double totalVolume = c1.getVolume() + c2.getVolume();
17
18     double newLength = std::pow( totalVolume, 1.0/3.0 );
19
20     Cube result(newLength);
21     return result;
22 }

```

By default, arguments are “passed by value” to a function. This means that:

- 
- 

## Alternative #1: Pass by Pointer

```

joinCubes-byPointer.cpp
15 Cube joinCubes(Cube * c1, Cube * c2) {
16     double totalVolume = c1->getVolume() + c2->getVolume();
17
18     double newLength = std::pow( totalVolume, 1.0/3.0 );
19
20     Cube result(newLength);
21     return result;
22 }

```

## Alternative #2: Pass by Reference

```

joinCubes-byReference.cpp
15 Cube joinCubes(Cube & c1, Cube & c2) {
16     double totalVolume = c1.getVolume() + c2.getVolume();
17
18     double newLength = std::pow( totalVolume, 1.0/3.0 );
19
20     Cube result(newLength);
21     return result;
22 }

```

## Contrasting the three methods:

	By Value	By Pointer	By Reference
Exactly what is copied when the function is invoked?			
Does modification of the passed in object modify the caller's object?			
Is there always a valid object passed in to the function?			
Speed			
Safety			

## Using the const keyword

### 1. Using const in function parameters:

joinCubes-by*-const.cpp	
15	Cube joinCubes(const Cube s1, const Cube s2)
15	Cube joinCubes(const Cube *s1, const Cube *s2)
15	Cube joinCubes(const Cube &s1, const Cube &s2)

**Best Practice:** “All parameters passed by reference must be labeled const.”  
– Google C++ Style Guide

### 2. Using const as part of a member functions’ declaration:

Cube.h	
1	#pragma once
2	
3	namespace cs225 {
4	class Cube {
5	public:
6	Cube();
7	Cube(double length);
8	double getVolume() ;
9	double getSurfaceArea() ;
10	
11	private:
12	double length_;
13	};
14	}

Cube.cpp	
...	
11	double Cube::getVolume() {
12	return length_ * length_ * length_;
13	}
14	
15	double Cube::getSurfaceArea() {
16	return 6 * length_ * length_;
17	}
...	

## Returning from a function

Identical to passing into a function, we also have three choices on how memory is used when returning from a function:

Return by value:

15	Cube joinCubes(const Cube &s1, const Cube &s2)
----	--

Return by reference:

15	Cube &joinCubes(const Cube &s1, const Cube &s2)
----	---

...remember: never return a reference to stack memory!

Return by pointer:

15	Cube *joinCubes(const Cube &s1, const Cube &s2)
----	---

...remember: never return a reference to stack memory!

## Copy Constructor

When a non-primitive variable is passed/returned **by value**, a copy must be made. As with a constructor, an automatic copy constructor is provided for you if you choose not to define one:

All **copy constructors** will:

The **automatic copy constructor**:

- 1.
- 2.

To define a **custom copy constructor**:

Cube.h	
4	class Cube {
5	public:
...	// ...
9	Cube(const Cube & other); // custom copy ctor

## CS 225 – Things To Be Doing:

1. Quiz 0 is ongoing
2. lab\_debug due Wednesday (11:59pm)
3. MP1 due Wednesday (11:59pm)
4. Daily POTDs every weekday